



Easy Lift SC

Super Concentrated Floor Finish Stripping Solution Removador de Acabados

DESCRIPTION

A professional strength floor stripper formulated to remove floor finish that has been UHS burnished on a single pass.

DIRECTIONS

Dilute stripper with cold water at the following recommendations:

LIGHT DUTY REMOVAL: Use a dilution ratio of 1:30 (4 oz per gallon).

NORMAL REMOVAL: Use a dilution ratio of 1:20 (6 oz per gallon).

HEAVY DUTY REMOVAL: Use a dilution ratio of 1:10 (13 oz per gallon).

- Apply liberal amounts of solution uniformly to floor with a mop.
- Let stripper solution soak for 10 minutes. **DO NOT ALLOW SOLUTION TO DRY ON FLOOR.**
- Scrub floor with and automatic scrubber or stripping machine.
- Use an automatic scrubber or wet vac to pick up dirty solution.
- Mop up any tracks left by automatic scrubbers before they dry.
- Rinse thoroughly and detail mop floor with clean water and and a clean mop.
- Let floor dry completely before applying floor finish.

NOTE: Test floor for color fastness in an inconspicuous area. Floors may become very slippery. Wear appropriate non-slip safety shoes. This product should not be used in contact with wood, rubber, painted surfaces or on asphalt or asbestos tile.

KEEP FROM FREEZING.



APPLICATIONS

FLOOR FINISH STRIPPER FOR:

> Most water based floor finishes

SPECIFICATIONS

Color Dark Green

Fragrance None

pH Range 12.0 - 12.5

Dilution 4 - 13 oz / gal.

Density 8.59

PACKAGING

6/1 quart

MPL-1135-61Q



5109 N National Dr. Knoxville TN 37914
888.722.5508 | www.cleanfreak.com

MPL-1135-61Q | 06-23-23

